

Declaration of Performance (DoP) in acc. with

**Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (No. 465)
Construction Products (Amendment etc.) (EU Exit) Regulations 2020 (No. 1359)**

No. ILGS355ML-UKCA-10025-01112022

1. Unique identification code of the product Type:

Plate S355ML / 1.8834 in accordance with EN 10025-4

2. Intended use(s):

Metallic structure, metallic- / concrete composite construction

3. Name, registered trade name or registered trademark and contact address of the manufacturer:

**Ilseburger Grobblech GmbH
Veckenstedter Weg 10
38871 Ilseburg, Germany
Tel.: +49 (0) 39452 85 - 0
Fax: +49 (0) 39452 85 - 8161
www.ilseburger-grobblech.de**

4. Name and contact address of the authorised representative whose mandate covers the tasks:

- not applicable -

5. System or systems of assessment and verification of constancy of performance of the construction product:

System 2+

6. Declaration of performance concerning a construction product covered by a harmonised standard:

Approved Body -TÜV UK Ltd (No. UKAB 0879) - performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control in accordance with annex ZA of EN 10025-1:2004.



7. Declared Performance:

Essential characteristic	Performance								Harmonised technical specification
Tolerances on dimensions and shape	see supplementary sheet 1								EN 10025-1:2004
Yield strength	Nominal thickness (mm)		Values (MPa)						
	>	≤	≥						
		16	355						
	16	40	345						
	40	63	335						
	63	80	325						
	80	100	325						
	100	150	320						
Tensile strength	Nominal thickness (mm)		Values (MPa)						
	>	≤	≥			≤			
		40	470			630			
	40	63	450			610			
	63	80	440			600			
	80	100	440			600			
	100	150	430			590			
Elongation	Nominal thickness (mm)		Values (%)						
	>	≤	≥						
		150	22						
Impact energy	Nominal thickness (mm)		Values (J) Temp. (°C)						
			+20	0	-10	-20	-30	-40	-50
		≤	≥						
		150	63	55	51	47	40	31	27
Weldability	Nominal thickness (mm)		CEV (%)						
	>	≤				≤			
		16				0,39			
	16	40				0,39			
	40	63				0,40			
	63	150				0,45			



Essential characteristic	Performance					Harmonised technical specification	
Durability	Nominal thickness (mm)		Ladle analysis (%)			EN 10025-1:2004	
		≤		≥	≤		
		150	C		0,14		
			Si		0,50		
			Mn		1,60		
			P		0,025		
			S		0,020		
			Nb		0,05		
			V		0,10		
			Al ges.	0,02			
			Ti		0,05		
			Cr		0,30		
			Ni		0,50		
			Mo		0,10		
	Cu			0,55			
	N		0,015				

The performance of the product named above is in conformity with the declared performances.
This declaration of performance is issued under the sole responsibility of the above-mentioned manufacturer.

Signed for and on behalf of the manufacturer by:

Ilseburg, 01.11.2022

Dipl.-Ing. Andreas Rost
Head of Order Management and Technical Service